



DESIGNATOR	A MIN	B MAX	C MIN	ANSI SIZE
FWC06a	6.65	18.80	1.20	6
FWC08a	8.90	25.40	1.60	8
FWC10a	10.85	28.00	2.00	10
FWC12a	13.30	34.00	2.50	12
FWC14a	15.25	39.00	2.50	14
FWC16a	17.25	44.00	3.00	16
FWC20a	21.80	50.00	3.50	20
FWC24a	25.60	56.00	4.00	24
FWC30a	32.40	72.00	4.50	30
FWC36a	38.30	90.00	5.00	36

PLAIN ROUND WASHER

FWC06a-36a

SHEET NO.

REF. NO.

1 of 2

F-13-73

SPECIFICATIONS

Plain round steel washers shall be manufactured according to the dimensions and tolerances in ANSI B18.22M for regular series washers. Unless corrosion resistant steel is used, washers shall be zinc-coated according to AASHTO M232 (ASTM A153) for Class D or AASHTO M298 (ASTM B695) for Class 50.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

Plain round steel washers are used in a variety of applications in several barrier systems. These washers are usually used with standard-strength bolts and nuts as shown in this guide for FBX06a-36a.

PLAIN ROUND WASHER

FWC06a-36a

SHEET NO.

DATE

2 of 2

03-23-00

